



GUIDE TO USING OUR AEROSOL KIT

- 1 SHAKE THE AEROSOL THOROUGHLY AND CHECK THE COLOUR BY SPRAYING A TEST CARD AND CHECKING TO THE CAR. A SMALL PIECE OF CARDBOARD WILL DO.**
- 2 DEPENDING ON HOW BAD THE SCRATCH OR DAMAGE IS ,A BODYFILLER MAY BE REQUIRED.**
- 3 MASK THE AREA TO BE PAINTED TO AVOID UNWANTED OVERSPRAY . APPLY A COAT OF PRIMER TO THE SURFACE FROM A DISTANCE OF 12 INCHES APPROX.[30 CMS.] WAIT TEN MINUTES AND APPLY A SECOND COAT IF REQUIRED. ALLOW THE PRIMER TO DRY ,1 HOUR APPROX.**
- 4 USING A FINE WET AND DRY PAPER, [WET THE PAPER], SAND THE PRIMER WITH A CIRCULAR MOTION UNTIL YOU HAVE A SMOOTH SURFACE FOR THE COLOUR TO BE APPLIED ON. DRY AND CLEAN THE AREA WITH THE PRECLEANER.**
- 5 APPLY THE COLOUR FROM A DISTANCE OF 12 INCHES . APPLY A NUMBER OF LIGHT COATS UNTIL YOU ARE HAPPY WITH THE COLOUR .LEAVE 5 MINUTES BETWEEN EACH COAT AND KEEP THE CAN MOVING FROM SIDE TO SIDE DURING APPLICATION. ALLOW THE PAINT TO DRY THOROUGHLY.**
- 6 APPLY A LIGHT COAT OF LACQUER FOLLOWED BY A FULL COAT [LEAVE FIVE MINUTES BETWEEN COATS] FROM A DISTANCE OF 12 INCHES. KEEP THE CAN MOVING FROM SIDE TO SIDE DURING APPLICATION.**
- 7 LEAVE 24 HOURS TO DRY BEFORE POLISHING WITH LIQUID COMPOUND TO BLEND THE OLD PAINTWORK WITH THE NEW.**

**A SUITABLE MASK SHOULD BE WORN WHEN
SPRAYING WITH AEROSOLS**